PROPAC 1+2

Specifications

Battery Pack		Propac 1	Propac 2
Lamp head sockets (splash proof) for Profilux Plus units		2	2
Obtainable performances with 1 Profilux Plus unit	max. Ws	200/400/600	200/400/600
Obtainable performances with 2 Profilux Plus units	max. Ws	400/600/800/ 1000/1200	400/600/800/ 1000/1200
Modeling light operation with "Auto-off" feature*		Yes	Yes
Number of Flashes with 1 x Profilux Plus 200 at full output**		1400	3200
Number of Flashes with 1 x Profilux Plus 400 at full output**		700	1600
Number of Flashes with 1 x Profilux Plus 600 at full output**		350	800
Recycling time with 1 and 2 Profilux Plus 200 at full output	sec	0,9	0,9
Recycling time with 1 and 2 Profilux Plus 400 at full output	sec	1,8	1,8
Recycling time with 1 and 2 Profilux Plus 600 at full output	sec	3,2	3,2
Recharge time at 110 V/230 V when fully discharged	hrs	4	4,5
Dimensions (WxLxH)	mm	166 x 219 x 210	166 x 219 x 296
Weight	kg	8,8	12

*If a connected Profilux Plus unit isn´t fired for 15 sec, the modeling light switches off automatically in order to preserve battery power. The modeling light turns on as soon as the unit is fired again.

**Battery pack fully charged, modeling light off, flash count halves with two units connected.

Tolerances of specifications and components conforming to DIN and IEC standards. Specifications are subject to change without notice.

MULTIBLITZ DR. ING. D. A. MANNESMANN GMBH | FERDINAND - PORSCHE - STRASSE 19 | D-51149 KÖLN | GERMANY | FON: +49 (0) 2203 - 93 96 10 | FAX: +49 (0) 2203 - 93 96 49
E-MAIL: INFO@MULTIBLITZ.DE | INTERNET: WWW.MULTIBLITZ.DE

Multiblitz + MADE IN GERMANY